



HAI0108DE-T

108" LED ALL-IN-ONE DISPLAY

The Hisense 108" interactive LED all-in-one features advanced touch technology, a smart whiteboard, wireless screen sharing, and cloud management to streamline collaboration and operation. Its vibrant, cinema-grade color reproduction, high brightness, and eye comfort technology enhance the user experience, while its energy-efficient design reduces costs, making it an ideal choice for dedicated spaces.

Highlights



108" COB Touchscreen Display

Featuring 20-point infrared touch technology for precise control, this height-adjustable screen effortlessly lowers to half its height to suits all users. Offering flexible dual mounting options—wall-mount or mobile cart—for effortless adaptability for dynamic collaborative spaces.



Smart Whiteboard

With the integrated smart whiteboard, collaborating and brainstorming become effortlessly efficient: erase the entire surface with a palm swipe; experience freehand sketches auto-correct into precise shapes; and instantly convert handwritten notes into digital formats with a single scan.



Effortless Transmission

This wireless screen-sharing solution enables instant quad-split screen and supports reverse screen casting for seamless collaboration, with compatibility across Windows, Android, and mac OS systems.



Streamlined Deployment

Pre-installed at the factory, the Hisense all-in-one achieves operation-ready deployment with a two-person team completing installation in under 90 minutes. Its self-configuring system eliminates technical barriers, while front access for all service needs ensures zero downtime mission-critical operations.



Dual Chip-Driven Precision Unleashed

Powered by a dedicated ASIC chip and HiView imaging engine, this display achieves over 105% DCI-P3 cinema-grade color delivering breathtaking vibrancy. Its 1,600-nit peak brightness enhances contrast, making bright images vivid and revealing hidden details in dark scenes.



Eye-Comfort Optimization

Hisense's self-developed anti-glare LED coating reduces ambient light impact. Combined with Camera Mode's random scanning overcoming sequential limits, it alleviates eye strain from extended use.



Built-in VisionInfo

Hisense VisionInfo integrates cloud-based remote management of displays, enabling centralized control and content distribution across dedicated screens to streamline professional digital operations.



Energy Efficient

Efficient power supply and 3-in-1 ASIC architecture reduce energy consumption; optimized common cathode drivers and energy-saving algorithms cut power by over 35% versus conventional COB, largely slashes operational costs.

Specifications

Physical

Pixel Pitch	1.25 mm
Pixel Configuration	Flip-chip COB (1 red, 1 green, 1 blue)
Screen Resolution (WxH)	1,920 x 1,080
Module Dimensions (WxH)	150 x 337.5 mm / 5.9 x 13.3 inch
No. of Modules Per Screen (WxH)	16 x 4 (Total 64 Pcs LED Modules)
Screen Dimensions (WxHxD) (With Screen Frame)	2,439 x 1,474 x 53 mm 96.02 x 58.03 x 2.09 inch
Product Dimensions (WxHxD) (With Mobile Cart)	2,439 x 2,004 x 1,038.85 mm 96.02 x 78.90 x 40.90 inch
Panel Dimensions (WxHxD)	600 x 337.5 x 31.5 mm 23.6 x 13.3 x 1.24 inch
Weight (per panel / screen)	4 kg / 81 kg / 8.82 lbs / 178.57 lbs
Pixel Density	640,000 pixels/m ²
Flatness of Cabinet (mm/inch)	± 0.05 mm
Cabinet Material	Die-cast Aluminum
Gray Level	14 bits
Colour Gamut	>105% DCI-P3
Aspect Ratio	16:9
Service Access	Front

Optical

Brightness (max./peak.)	1,000 / 1,600 nits
Brightness - Default (Adjustable)	600 (100-1,000) nits
Contrast Ratio	25,000 : 1@10lux
Visual Viewing Angle (HxV)	165° x 150°
Brightness Uniformity	98%
Color Uniformity	± 0.003 Cx,Cy
Processing Depth	14 bits
Color Temp - Default (Adjustable)	6,500 K (2,000 ~ 9,300 K)

Electrical

Power Supply Voltage	100-240V, 50/60Hz
Average Power Consumption (W/Screen)	≤430 @ 1,000 nits ≤385 @ 600 nits
Max Power Consumption (W/Screen)	≤1,060 @ 1,000 nits ≤730 @ 600 nits
Refresh Rate	3,840 Hz (typ.)

Touch

Sensing Type	Infrared Touch Frame
Infrared Touch	≤20 points Android / Windows: 20 points; MAC: Single Point
Touch Accuracy	±1 mm (90%)
Theory Clicks	Unlimited
Minimum Touch Object	≥6 mm
Writing Height	≤8 mm
Windows 11/10/8/7, Android	Multi Touch

Connectivity

Wi-Fi	2.4G & 5G
Bluetooth	5.0
Input	HDMI(2.0) IN x3 (include 1 internal) USB 2.0 x1 Type-C (Not full function) x1 OPS not supported RS232 x1 LAN x1
Output	HDMI (2.0) x1 (HDMI IN2 signal compatible) SPDIF x1
Speaker (Built-In)	10 W x2

Operation Conditions

Operating Temp/Humidity	0 - 40°C / 10% - 90%RH (no frost)
Storage Temp/Humidity	-20 - 40°C / 10% - 65%RH (no frost)
Expected LED Lifetime (typ)	100,000 Hrs

System

OS	Android 9.0
CPU	CA73*4 1.3GHz
GPU	G52 MC1
DDR	3GB
ROM	64GB
Language	Chinese / English (Default) / French / German / Spanish / Italian / Polish / Arabic / Russian

Package Solution

Packing Method	Flight case for cabinets / modules / wall bracket & accessory
Packaging Dimensions (W x H x D)	1,069 x 1,745 x 762 mm 42.09 x 68.7 x 30 inch
Net / Gross Weight (w Wall Bracket)	75 kg / 210 kg 165.35 lbs / 462.97 lbs

Mobile Cart (Optional) & Accessories






Packing Method	Wooden Box (For Mobile Cart) (Optional)
Packaging Dimensions (W x H x D)	1,645 x 240 x 965 mm 64.76 x 9.45 x 37.99 inch
Net / Gross Weight	31.5 kg / 64 kg 69.45 lbs / 141.1 lbs
Standard Accessory	User Manual / Remote Control / Battery / Vacuum Tool / Wall Bracket
Optional Accessory	Mobile Cart (LG400301A) Hisense Dongle (HT007E)

Certification

Standard Certification	CE, CB, FCC, cTUVus, EAC
------------------------	--------------------------

Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Dimensions



Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.