



## HT007E

### WIRELESS SCREEN TRANSMISSION

The HT007E wireless screen transmission dongle connects to the USB-C port of a device and transmits the on-screen content to the Digital Whiteboard for everyone to see. Connect it to your device and with a single button press, the content will be instantly displayed on the whiteboard through fast and stable streaming (Windows / Mac supported).

#### Highlights



#### 4K UHD Transmission

Enable attendees to easily see what is being shared on the screen. This clear screen sharing feature makes it easy to create everything you need for an engaging work and study environment.



#### Super Stable Streaming

Continuous and smooth screen sharing for a better meeting experience. This stable connection empowers your efficient meetings.



#### Fast Connection

With 3s rapid connection, you can start a meeting instantly. And your display will remember the HT007E the next time you connect.



#### Wireless and Network-free Sharing

No need for wired or wireless network, no need to install any applications. You can get away from traditional screen sharing devices and use wireless casting dongle anytime, anywhere.

### Specifications

#### HT007E

|                       |                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Color                 | Black                                                                                                                                      |
| Logo                  | Hisense                                                                                                                                    |
| Connect Number        | 1 received device (same time)                                                                                                              |
| Button                | 1                                                                                                                                          |
| Port                  | Type-C                                                                                                                                     |
| Working Voltage       | 5V                                                                                                                                         |
| Video Resolution      | 4K30Hz                                                                                                                                     |
| Transmission Distance | 15m                                                                                                                                        |
| Plug and Play         | Support                                                                                                                                    |
| WiFi Module           | IEEE 802.11b/g/n/ac                                                                                                                        |
| Indicator Light       | 1. Blinking when connecting<br>2. White color when using                                                                                   |
| Certification         | cTUVus+CB / FCC SDOc+IC SDOc / FCC ID+IC ID / CE-RED / UKCA / REACH / RoHS                                                                 |
| Hot Plug              | Support                                                                                                                                    |
| Working Temperature   | -10°C ~ +45°C                                                                                                                              |
| Working Humidity      | ≤95%                                                                                                                                       |
| Adaptive Model        | 65MR6DE / 75MR6DE / 86MR6DE / 65MR6DE-E / 75MR6DE-E / 86MR6DE-E / 65MR61DE-E / 75MR61DE-E / 86MR61DE-E / HAI0108DE / HAI0136DE / HAI0163DE |

\*Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Learn More: [www.hisense-b2b.com](http://www.hisense-b2b.com) | Contact Us: [sales@hisense-b2b.com](mailto:sales@hisense-b2b.com)

[in](#) @Hisense B2B Europe | @Hisense B2B USA | @Hisense B2B MENA | @Hisense B2B Indonesia | @Hisense B2B South Africa | @Hisense B2B Australia